

# Avalon LED Striplight AVNL Series

# **Features**

This low profile, clean appearance, surface mounted striplight provides high light levels with a white acrylic diffuser. Available in 2 ft., 4 ft., and 8 ft. lengths. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to a standard junction box (not included) on a ceiling or wall.

# LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE









# Construction

Housing is die-formed of 22-gauge steel. Power supply connections must be made inside the junction box (not included).

# Finish

Pre-finished white steel housing.

# Diffuser

White acrylic.

## **Electrical**

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. 0-10 V dimming.

# **LED**

Integrated LED modules capable of producing: 25W = 2500 delivered lumens 43W = 4000 delivered lumens 76W = 7900 delivered lumens Adjustable CCT - 3000K/4000K/5000K Rated for 50,000 hours, 90 CRI.

# **Options**

Emergency Battery Back-Up (-BB) Motion Sensor (-MS) Emergency Battery Back-Up with Motion Sensor (-MSBB)


# Certification

cETLus listed for indoor damp locations.

# Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.



# **Ordering Information:**

		Delivered				
White	LED	Lumens	Adjustable CCT	L	W	D
AVNL2430LAJD2WH	25W	2500	3000K/4000K/5000K	24"	2-1/4"	2-3/4"
AVNL4848LAJD2WH	43W	4000	3000K/4000K/5000K	48"	2-1/4"	2-3/4"
AVNL4848LAJD2WH-BB	43W	4000	3000K/4000K/5000K	48"	2-1/4"	2-3/4"
AVNL4848LAJD2WH-MS	43W	4000	3000K/4000K/5000K	48"	2-1/4"	2-3/4"
AVNL4848LAJD2WH-MSBB	43W	4000	3000K/4000K/5000K	48"	2-1/4"	2-3/4"
AVNL9685LAJD2WH	76W	7900	3000K/4000K/5000K	96"	2-1/4"	2-3/4"
AVNL9685LAJD2WH-BB	76W	7900	3000K/4000K/5000K	96"	2-1/4"	2-3/4"
AVNL9685LAJD2WH-MS	76W	7900	3000K/4000K/5000K	96"	2-1/4"	2-3/4"
AVNL9685LAJD2WH-MSBB	76W	7900	3000K/4000K/5000K	96"	2-1/4"	2-3/4"