

Core Fixed Rail CRRF Series

Features

This decorative dimmable fixed rail features reliable high-performance LEDs. Heads swivel and pivot to direct light where needed. Applications that this fixture could fit well include: kitchens, retail environments, and anywhere that needs highlighted illumination. The fixture mounts to a standard junction box (not included). These fixtures mount to the ceiling or wall.

Construction

The canopy is 22-gauge stamped steel and the rail is made of 20-gauge steel tube. Power supply connections must be made inside a junction box (not included).

Finish

The canopy, rail, and individual rail heads are painted in black or plated in satin nickel finish with a clear lacquer topcoat.

Diffuser

Frosted acrylic diffuser.

Electrical

Input 120 VAC / 60HZ. Compatible with TRIAC and ELV dimmers.

LED

Fixture includes 4 or 6 integrated LED modules capable of producing: 4-Light - 26W = 2600 source lumens, 1800 delivered lumens 6- Light - 40W = 4000 source lumens, 2700 delivered lumens 3000K (CCT). Rated for 50,000 hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ENERGY STAR® Qualified Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.


Specifications and dimensions


subject to change without notice.

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	









Ordering Information:

			Source	Delivered	1			
Black	Satin Nickel	LED	Lumens	Lumens	CCT	L	W	н
CRRF4450L30BK	CRRF4450L30SN	26W	2600	1800	3000K	36-3/8"	5-3/8″	6-1/4″
CRRF6450L30BK	CRRF6450L30SN	40W	4000	2700	3000K	55-1/8″	5-1/4″	7-1/2″