

# **Edge Round LED Surface Mount Disc Light EGRF Series**

# DATE PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE











# **Features**

This ultra low profile design provides a dramatic look and features an edge-lit light panel construction. Products can be used in various applications including corridors, closets, bath, showers, hallway, kitchen and anywhere general lighting is needed. Indoor use only - Wall or ceiling mount.

Outdoor use only - Covered ceiling mount.

## Construction

Edge-lit technology housing is injection molded with aluminum backplate. Snap-in bracket.

Mounts to standard junction box (not included).

Power supply connections must be made inside junction box.

#### **Finish**

Choose from white, satin nickel, or black finish.

#### Diffuser

White acrylic.

#### **Electrical**

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable down to 10% of full scale with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

# Lamping

Fixture includes a LED modules capable of producing:

12W = 1200 source lumens, 720 delivered lumens

15W = 1500 source lumens, 1000 delivered lumens

22W = 2200 source lumens, 1690 delivered lumens

Adjustable Choice 3000K, 4000K, 5000K (CCT).

Rated 24/7, working temperature: -20°C ~ 45°C for 50,000 Hrs. 90 CRI.

### Certification

cETLus listed ENERGY STAR® Qualified Title 24/JA8 Compliant

Wet location rated for indoor use. Outdoor wet location rated for covered ceiling mount applications ONLY (not recommended for any other outdoor use). Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

# **Options - Sold Separately**

Retrofit Kit for 4" and 6" ceiling cans. Battery back-up (EGRF-BB08) for 8" models. Spacer Pan (EGRF-BB08PAN) for 8" models.

#### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

#### Accessory Kit



EGRF-RET04 For use in converting 4 in. round ceiling cans



EGRF-RET06 For use in converting 6 in. round ceiling cans



EGRF-BB08 Battery back-up (8 in. model only)



EGRF-BB08PAN Spacing Pan (8 in. model only)

# **Ordering Information:**

•		Source	Delivered					
Satin Nickel	White	Black	LED	Lumens	Lumens	Adjustable CCT	DIA.	D
EGRF06LAJD1SN	EGRF06LAJD1WH	EGRF06LAJD1BK	12W	900	745	3000K/4000K/5000K	5-3/8"	3/4"
EGRF08LAJD1SN	EGRF08LAJD1WH	EGRF08LAJD1BK	15W	1125	1034	3000K/4000K/5000K	8"	3/4"
EGRF12LAJD1SN	EGRF12LAJD1WH	EGRF12LAJD1BK	22W	1650	1575	3000K/4000K/5000K	12"	3/4"

