

Elm LED Outdoor Ceiling ELMW Series

Features

This outdoor LED light is ideal for security and general lighting. 3 in 1 color temperature adjustable option. Provides down-light illumination for outdoor or indoor residential, commercial, and hospitality applications. Fixture mounts to a standard junction box (not included).

Construction

Die-cast aluminum housing. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black powder coated finish.

Diffuser

Solid acrylic diffuser.

Electrical

Input 120-277 VAC / 60 Hz. 0-10V dimming (120-277V) TRIAC and ELV dimming (120V only) Minimum starting temp -4° F/ -20°C.

LED

Integrated LED modules capable of producing: 15W = 845 delivered lumens 20W = 1125 delivered lumens Adjustable CCT - 3000K/4000K/5000K Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for wet locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

		Delivered			
Black	LED	Lumens	Adjustable CCT	D	DIA.
ELMW09LAJUDBK	15W	845	3000K/4000K/5000K	2-1/2"	9"
ELMW/11LA ILIDBK	201//	1125	3000K/4000K/5000K	2-1/2"	11"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	











