



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Gale LED Outdoor Sconce GLEW Series



### Features

Ideal use for security and general lighting in outdoor residential, commercial, and hospitality applications. Vertical or horizontal mounting. Fixture mounts to a standard junction box (not included).

### Construction

Durable metal construction with powder coat finish. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

### Finish

Black or Textured Grey.

### Diffuser

White frosted glass diffuser.

### Electrical

Input 120-277 VAC / 60 Hz.  
0-10V dimming (120-277V), TRIAC (120V).  
Minimum starting temp -4° F / -20°C.

### LED

Integrated LED modules capable of producing:  
25W = 1425 delivered lumens  
29W = 1663 delivered lumens  
35W = 2400 delivered lumens  
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

### Certification

All fixtures are cETLus listed for wet locations.  
Title 24/JA8 Compliant (outdoor only).

### Option

Emergency battery back-up (24" and 36" ONLY\*) Add -BB to end of part number.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions**  
subject to change without notice.

## Ordering Information:

Black	Textured Grey	LED	Delivered Lumens	CCT	H	W	D
GLEW0518L30UDBK	GLEW0518L30UDTG	25W	1425	3000K	18"	4-1/2"	2-1/2"
GLEW0524L30UDBK*	GLEW0524L30UDTG*	29W	1663	3000K	24"	4-1/2"	2-1/2"
GLEW0536L30UDBK*	GLEW0536L30UDTG*	35W	2400	3000K	36"	4-1/2"	2-1/2"

