



Bailey LED Ceiling BAYF Series

Features

Decorative ceiling fixture with a metal finish and a white acrylic diffuser. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Bi-Level Motion Sensor (Optional '-MS') EXCLUDES 12"*

- Built-in daylight sensor
- Detection area, time delay and daylight threshold can be precisely set via DIP switch
- Wide detection area, range up to 50 ft. (16 m) max

Emergency Back-Up (Optional '-BB') EXCLUDES 12"*

- 90 minute run-time
- 7.4V 2500 mAh Lithium Ion Battery
- 4 watts and 8 watts

Construction

Die-formed steel construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black or Satin Nickel.

Diffuser

White acrylic.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
20W = 1600 delivered lumens
26W = 1800 delivered lumens
30W = 2000 delivered lumens
35W = 2100 delivered lumens
45W = 2700 delivered lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Products ordered with battery back-up:

Fixture must be installed and the battery energized within six months of the purchase date to remain eligible for warranty coverage. Failure to comply may result in complete battery discharge, rendering it irrecoverable and thereby voiding the warranty.

Specifications and dimensions subject to change without notice.

Ordering Information:

Black	Satin Nickel	LED	Delivered Lumens	Adjustable CCT	DIA.	D
BAYF12LAJUDBK*	BAYF12LAJUDSN*	20W	1600	2700K/3000K/3500K/4000K/5000K	12"	2-1/2"
BAYF14LAJUDBK	BAYF14LAJUDSN	26W	1800	2700K/3000K/3500K/4000K/5000K	14"	2-1/2"
BAYF19LAJUDBK	BAYF19LAJUDSN	30W	2000	2700K/3000K/3500K/4000K/5000K	19"	2-1/2"
BAYF24LAJUDBK	BAYF24LAJUDSN	35W	2100	2700K/3000K/3500K/4000K/5000K	24"	4"
BAYF30LAJUDBK	BAYF30LAJUDSN	45W	2700	2700K/3000K/3500K/4000K/5000K	30"	4"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



24"



30"

