



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Beam LED Outdoor Sconce BEAW Series

Features

Modern design. Horizontal or vertical mounting.
Provides lighting in residential, commercial, and hospitality applications.
Fixture mounts to standard junction box (not included).



Emergency Back-Up (Optional '-BB')

- 90 minute run-time
- 9.6VDC LiFePO4 battery
- 8 watts

Construction

Aluminum housing. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black powder coated finish.

Diffuser

Clear seeded acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.
Minimum starting temp -4° F / -20°C

Lamping

Fixture includes a LED modules capable of producing:
10W = 450 delivered lumens
15W = 685 delivered lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs. 90 CRI..

Certification

All fixtures are cETLus listed for wet locations.
ADA compliant
Title 24/JA8 Compliant

Warranty

5 Year Limited Warranty:

Restrictions apply based on location.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Black	LED	Delivered Lumens	Adjustable CCT	H	W	D
BEAW0512LAJUDBK	10W	450	2700K/3000K/3500K/4000K/5000K	12"	4-3/4"	3"
BEAW0512LAJUDBK-BB	10W	450	2700K/3000K/3500K/4000K/5000K	12"	4-3/4"	3"
BEAW0518LAJUDBK	15W	685	2700K/3000K/3500K/4000K/5000K	18"	4-3/4"	3"
BEAW0518LAJUDBK-BB	15W	685	2700K/3000K/3500K/4000K/5000K	18"	4-3/4"	3"

