

Cirrus LED Flush Mount - Universal Driver C2F Series

Features

A round floating cloud style with a white diffuser. Adjustable output on 14" model. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Emergency Back-Up (Optional '-BB') Excludes 11"

- 90 minute run-time
- 7.4V 2500 mAh Lithium Ion Battery
- 8 watts

Construction

A 22-gauge steel housing made by stamping process and painted in lighting grade white. Standard mounting holes and hardware included. Power supply connections must be made inside a junction box (not included).

Finish

White finish.

Diffuser

Smooth white acrylic diffuser.

Electrical

Input 120-277VAC / 60 Hz. 0-10V dimming (120-277V), TRIAC/ELV (120V)

LED

Integrated LED modules capable of producing: 11" - 17W = 1520 delivered lumens 14" - 17/34W = 1360/2690 delivered lumens 19" - 34W = 2930 delivered lumens Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. T24-JA8 Compliant. Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

	Delivered			
LED	Lumens	Adjustable CCT	DIA.	D
17W	1520	2700K/3000K/3500K/4000K/5000K	11″	3-1/4″
17W/34W	1360/2690	2700K/3000K/3500K/4000K/5000K	14″	3-3/8"
17W/34W	1360/2690	2700K/3000K/3500K/4000K/5000K	14″	3-3/8″
34W	2930	2700K/3000K/3500K/4000K/5000K	19″	3-3/8″
34W	2930	2700K/3000K/3500K/4000K/5000K	19″	3-3/8″
	17W 17W/34W 17W/34W 34W	17W 1520 17W/34W 1360/2690 17W/34W 1360/2690 34W 2930	LED Lumens Adjustable CCT 17W 1520 2700K/3000K/3500K/4000K/5000K 17W/34W 1360/2690 2700K/3000K/3500K/4000K/5000K 17W/34W 1360/2690 2700K/3000K/3500K/4000K/5000K 34W 2930 2700K/3000K/3500K/4000K/5000K	LED Lumens Adjustable CCT DIA. 17W 1520 2700K/3000K/3500K/4000K/5000K 11" 17W/34W 1360/2690 2700K/3000K/3500K/4000K/5000K 14" 17W/34W 1360/2690 2700K/3000K/3500K/4000K/5000K 14" 34W 2930 2700K/3000K/3500K/4000K/5000K 19"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	







FLUSH MOUNT



BATTERY BACKUP