

Dakota LED Outdoor Sconce DKTW Series

Features

Simplistic design. Down light with wall wash effect. Ideal use in entrances or anywhere general outdoor lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are powder coated in Black, Bronze or White.

Diffuser

Frosted white glass bottom diffuser.

Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC. Minimum starting temp -4° F / -20°C

Lamping

Fixture includes an LED module capable of producing: 12W = 540 delivered lumens 24W = 1000 delivered lumens Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for wet locations.
ADA

Title 24/140 Compliant

Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE




















Ordering Information:

Denvered								
Black	Bronze	White	LED	Lumens	Adjustable CCT	Н	W	D
DKTW0504LAJUDBK	DKTW0504LAJUDBZ	DKTW0504LAJUDWH	12W	540	2700K/3000K/3500K/4000K/5000K	4-1/8"	4-7/8"	2-1/2"
DKTW0807LAJUDBK	DKTW0807LAJUDBZ	DKTW0807LAJUDWH	24W	1000	2700K/3000K/3500K/4000K/5000K	7"	8"	2-1/2"

Delivered