

Halo LED Pendant HLOP Series

Features

This pendant features with edge lit illumination.

Includes 9 ft. adjustable cord.

For use in kitchen, dining, foyers or anywhere general lighting is needed.

Provides lighting in residential, commercial and hospitality applications.

Fixture mounts to standard junction box (not included).

Construction

Steel canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Black and Light Antique Brass finish.

Diffuser

Frosted acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing: 18W = 1340 delivered lumens Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for damp locations. Title 24/JA8 Listed

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

DATE LOCATION **PREPARED** QUANTITY ΒY COMMENTS FIXTURE TYPE CATALOG NUMBER









Ordering Information:



