

Halo LED Multi Round Pendant HLOP Series

Features

This pendant features edge lit illumination. Includes 9 ft. adjustable cord. Provides lighting in residential, commercial and hospitality applications. This fixture mounts to a standard junction box (not included).

Construction

Steel canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included). Canopy - 18" DIA. \times 2" D or 24" DIA. \times 2" D

Finish

Black or Light Antique Brass finish.

Diffuser

Frosted acrylic diffusers.

Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing: 108W = 8040 delivered lumens 162W = 12060 delivered lumens Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5-year from date-of-purchase.


Specifications and dimensions subject to change without notice.

LOCATION		DATE
PREPARED		
BY		QUANTITY
P.		
COMMENTS		
		FIXTURE TYPE
CATALOG	_	
NUMBER		
1		











Delivered								
Black	Light Antique Brass	LED	Lumens	Adjustable CCT	Н	DIA.		
HLOPO8LAJUDBKRND6	HLOP08LAJUDLBRND6	108W	8040	2700K/3000K/3500K/4000K/5000K	9"	18"		
HI OPOSI A ILIDEKENIDO	HI ODORI A ILIDI RENDA	162\//	12060	2700K/3000K/3500K/4000K/5000K	Q"	24"		