

Liam LED Outdoor Sconce LEMW Series

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE











Features

Modern design. Provides lighting in residential, commercial, and hospitality applications. Fixture mounts to standard junction box (not included).

Emergency Back-Up (Optional '-BB') for 24"

- 90 minute run-time
- 9.6VDC LiFePO4 battery
- 8 watts

Construction

Aluminum housing. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black powder coated finish or Painted Nickel fiinish.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ. 0-10V dimming (120-277V), TRIAC (120V). Minimum starting temp -4° F / -20°C

Lamping

Fixture includes a LED modules capable of producing: 20W = 700 delivered lumens 25W = 875 delivered lumens Adjustable Color Temp: 2700K, 3000K, 3500K, 4000K or 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification


All fixtures are cETLus listed for wet locations. Title 24/JA8 Compliant

Warranty

5 Year Limited Warranty: Restrictions apply based on location.

Specifications and dimensions subject to change without notice.





Ordering Information:

Delivered								
	Black	Painted Nickel	LED	Lumens	Adjustable CCT	Н	W	D
	LEMW0518LAJUDBK	LEMW0518LAJUDNP	20W	700	2700K/3000K/3500K/4000K/5000K	18"	4-1/2"	5-1/2"
	LEMW0524LAJUDBK	LEMW0524LAJUDNP	25W	875	2700K/3000K/3500K/4000K/5000K	24"	4-1/2"	5-1/2"
	LEMW0524LAJUDBK-BB	LEMW0524LAJUDNP-BB	25W	875	2700K/3000K/3500K/4000K/5000K	24"	4-1/2"	5-1/2"