


LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	



Features

Simple style elegant geometry. Horizontal or vertical mounting. Provides lighting in residential, commercial and hospitality applications. This fixture mounts to a standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black or Satin Nickel finish.

Diffuser

Frosted white acrylic diffuser.

Electrical

Input 120-277 VAC / 60 Hz. 0-10V dimming (120-277V), TRIAC/ELV (120V)

LED

Integrated LED modules capable of producing: 18W = 1700 delivered lumens 26W = 2500 delivered lumens 34W = 3000 delivered lumens Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cULus listed for indoor damp locations. ADA Compliant T24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.



Ordering Information:

Delivered										
Black	Satin Nickel	LED	Lumens	Adjustable CCT	L	н	D			
LIAV2404LAJUDBK	LIAV2404LAJUDSN	18W	1700	2700K/3000K/3500K/4000K/5000K	24-3/4"	4-1/2"	4"			
	LIAV3604LAJUDSN		2500	2700K/3000K/3500K/4000K/5000K	36-3/4"	4-1/2"	4″			
LIAV4804LAJUDBK	LIAV4804LAJUDSN	34W	3000	2700K/3000K/3500K/4000K/5000K	48″	4-1/2"	4"			

