



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Poly LED Outdoor Sconce POLW Series

Features

Ideal use for general lighting in indoor or outdoor residential, commercial, and hospitality applications. 90° pivoting head, multiple knockouts for direct wire, integrated dusk-to-dawn photocell and adjustable wattage. Fixture can be mounted to a standard junction box (not included).



Construction

Die cast construction with weather resistant powder coating. Power supply connections must be made inside a junction box (not included).

Finish

Black, Bronze or White finish.

Diffuser

Clear glass diffuser.

Electrical

Input 120-277VAC / 60Hz.
Compatible with 0-10V dimmers.
Minimum starting temp -4° F/-20° C

LED (Adjustable Wattage)

Integrated LED modules capable of producing:
8" Model - 15W/20W/25W = 1950/2600/3250 delivered lumens
11" Model - 45W/60W/75W = 5850/7800/9750 delivered lumens
Adjustable Choice 3000K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for outdoor wet locations.
Title 24/J8A Compliant
ADA

Warranty


5 Year Limited Warranty:

Restrictions apply based on location.

**Specifications and dimensions
subject to change without notice.**



Adjustable from 0° to 90°



Ordering Information:

Black	Bronze	White	Adjustable LED	Delivered Adjustable Lumens	Adjustable CCT	H	W	D
POLW0708LAJD2BK	POLW0708LAJD2BZ	POLW0708LAJD2WH	15W/20W/25W	1950/2600/3250	3000K/4000K/5000K	8"	6-1/2"	4"
POLW0911LAJD2BK	POLW0911LAJD2BZ	POLW0911LAJD2WH	45W/60W/75W	5850/7800/9750	3000K/4000K/5000K	11"	8-1/2"	4-1/2"