



Rowan LED Outdoor Sconce RWNW Series

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		
CATALOG NUMBER		Fixture Type



Features

This LED light is ideal for security and general lighting. Provides lighting in residential, commercial, and hospitality applications. Fixture can be mounted horizontally or vertically to a standard junction box (not included).

Construction

Back pan is die formed from 22-gauge steel. All steel metal housing construction with sealed diffuser. Power supply connections must be made in a junction box (not included).

Finish

Metal housing is available in textured grey or textured bronze finish.

Diffuser

Diffuser is made of 0.10" thick standard white acrylic.

Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.

TRIAC and ELV dimming only at 120 VAC.

Minimum starting temp -4° F/-20° C

LED

Integrated LED modules capable of producing:

21W = 1230 source lumens, 1100 delivered lumens

37W = 2190 source lumens, 2360 delivered lumens

Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).

Rated for 50,000 Hrs., 90 CRI.

Certification

cETLus certified for wet locations.


Title 24/J8A Compliant

*ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
subject to change without notice.



Ordering Information:

Textured Bronze		Textured Grey		LED	Delivered Lumens	Delivered Adjustable CCT	H	W	D	MC
*RWNW0520LAJUDBZ		*RWNW0520LAJUDTG		21W	1230	2700K/3000K/3500K/4000K/5000K	20"	5"	3-1/2"	10"
RWNW0736LAJUDBZ		RWNW0736LAJUDTG		37W	2190	2700K/3000K/3500K/4000K/5000K	36"	7"	4-1/2"	18"