

Ryland LED Vanity RYDV Series

Features

Contemporary vanity in satin nickel finish. Provides lighting in residential, commerical or hospitality applications. Fixture can be mounted horizontally or vertically to a standard junction box (not included) on a wall.

Construction

The wiring channel is formed from 22-gauge steel and is provided with standard mounting holes and wiring access. Power supply connections must be made inside a junction box (not included).

Finish

Plated in satin nickel finish.

Diffuser White acrylic diffuser.

Electrical

Input 120-277VAC / 60Hz. Compatible with 0-10V dimmers.

LED

Intergrated LED modules capable of producing: 28 = 26W, 2200 source lumens, 1348 delivered lumens 38" = 37W, 3600 source lumens, 1907 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.





Limited Quantities Remain. Consult Factory.





Ordering Information:

| | | Source | Delivered | | | | |
|-------------------|-----|--------|-----------|-------|-----|----|--------|
| Satin Nickel | LED | Lumens | Lumens | ССТ | L | н | D |
| RYDV280422L30D2SN | 26W | 2200 | 1348 | 3000K | 28″ | 4" | 3-1/2" |
| RYDV380436L30D2SN | 38W | 3600 | 1907 | 3000K | 38″ | 4" | 3-1/2" |