

Slim Round LED Surface Mount Disc Light SLMF Adjustable Series

Features

This ultra low profile, flat back design, mimics the look of recessed lighting without the need for housings. Products can be used in various applications including corridors, closets, bath, showers, hallway, kitchen and anywhere general lighting is needed. Wall or ceiling mount.

Construction

Aluminum housing. Mounts to standard junction box (not included). Power supply connections must be made inside a 4" junction box. Mounting Center is 3-1/2" for Octagon box or 4-3/4" for Square box. Application only (without mud ring).

Finish

White finish.

Diffuser

White polystyrene diffuser.

Electrical

Direct wired, 120V AC with Driver-on-Board technology. Dimmable down to 10% of full scale with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

Lamping

Fixture includes a LED modules capable of producing: 15W = 900 delivered lumens
Adjustable choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

cETLus listed
Title 24/JA8 Compliant
Wet location rated for in

Wet location rated for indoor use.

Outdoor wet location rated for covered ceiling mount applications ONLY (not recommended for any other outdoor use).

Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.



















Ordering Information:

Delivered						
White	LED	Lumens	Adjustable CCT	DIA.	D	MC
SLMEOGLA ID1WH	15\\\/	900	2700K/3000K/3500K/4000K/5000K	7-1/2"	1-1/8"	3-1/2" (Octagon) or 4-3/4" (Square)