



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

View LED Pendant VIP Series



Features

Frosted glass cylinder inside a clear glass cylinder suspended with a 9 ft. cord. Mounts to a standard junction box (not included).

Construction

The outer glass cylinder is 16" tall and 4-3/4" in diameter and the inner glass cylinder is 14" tall and 3-7/8" in diameter. The unit is held into place by three decorative studs. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

The canopy is plated in black or satin nickel.

Diffuser

Inner white glass cylinder is 0.14" thick with clear outer glass.

Electrical

Input 120-277 VAC / 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
15W = 900 delivered lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are ETL listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions
subject to change without notice.**



Ordering Information:

Black	Satin Nickel	LED	Delivered Lumens	Adjustable CCT	DIA.	H
VIPO4LAJUDBKWH	VIPO4LAJUDSNWH	15W	900	2700K/3000K/3500K/4000K/5000K	4-3/4"	16"