



## Vasari LED Outdoor Sconce VSRW Series

### Features

Die-cast aluminum housing with clear seeded glass diffuser. Provides down-light illumination. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

### Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

### Finish

Black powder coat finish.

### Diffuser

Cleer seeded glass diffuser.

### Electrical

Input 120-277 VAC 60 HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.

TRIAC and ELV dimming only at 120 VAC.

Minimum starting temp. -4° F / -20° C.

### Lamping

Fixture includes a LED modules capable of producing:

12W = 460 delivered lumens

18W = 700 delivered lumens

Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).

Rated for 50,000 Hrs., 90 CRI.

### Certification

All fixtures are cETLus listed for wet locations.

Title 24/JA8 Compliant


### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions**  
subject to change without notice.

### Ordering Information:

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



Black	LED	Delivered Lumens	Adjustable CCT	H	W	D
VSRW0412LAJUDBK	12W	460	2700K/3000K/3500K/4000K/5000K	12"	4"	4"
VSRW0517LAJUDBK	18W	700	2700K/3000K/3500K/4000K/5000K	17"	5"	5-5/8"