



## Adjustable Wattage LED Vaportite

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

### Features

Designed for applications requiring an industrial grade fixture that can be used where dirt, dust, humidity, moisture and cold temperatures are present. The polycarbonate housing is fully gasketed. Includes mounting brackets and water tight connector.



### Option

Emergency Battery Back-Up (model # with -BB)  
9.5VDC LiFePO4 battery, 8 Watts, 90 minute run time.

### Construction

Impact resistant grey polycarbonate housing. Continuous gasket offers secure seal against dust and moisture. Power supply connections can be made inside fixture wire way or in a junction box (not included).

### Finish

Grey polycarbonate finish.

### Diffuser

White polycarbonate diffuser.

### Electrical

Input 120-277 VAC 60 HZ.  
Compatible with commercial (0-10V) dimmers.

### LED

Integrated LED modules capable of producing:  
Adjustable Wattage: 30W / 40W / 50W  
Delivered Lumens: 4500 / 6000 / 7500  
Adjustable CCT: 2700/3000/3500/4000/5000K  
Rated for 50,000 Hrs., 90 CRI.

### Certification

All fixtures are cETLus listed for indoor and outdoor wet locations.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

### Specifications and dimensions subject to change without notice.

## Ordering Information:

Grey VTL48AJLAJD2	Adjustable Wattage 30W/40W/50W VTL48AJLAJD2-BB	Delivered Lumens 4780/5940/7580 30W/40W/50W	Adjustable CCT 3000K/3500K/4000K/5000K/6500K 3000K/3500K/4000K/5000K/6500K	L 47-1/4" 47-1/4"	W 3-3/4" 3-3/4"	D 3-1/8" 3-1/8"